



EN 16510
 BlmSchV Stufe 2
 Regensburger BStV / Aachener BStV / Munchener BStV
 ART.15a B-VG / LRV
 5 stelle DM.186 / Conto Termico 2.0


Heating technical data

(Max) nominal heat output	6.2 kW
Minimum heat output	2.9 kW
Efficiency at Max	91 %
Efficiency at Min	92 %
Energy Efficiency Class (A++ / G scale)	A+
Energy Efficiency Index (EEI)	128 %
Seasonal space heating energy efficiency (η_s)	87 %
Temperature of exhaust smoke at Max	133 °C ***
Temperature of exhaust smoke at Min	86 °C ***
PM / OGC / NOx at Max (13% O ₂)	8 / 1 / 100 mg/Nm ³
PM / OGC / NOx at Min (13% O ₂)	10 / 1 / 97 mg/Nm ³
CO at 13% O ₂ at Min and at Max	0.011 / 0.008 %
CO ₂ at Min and at Max	9.9 / 13.8 %
Recommended draught at Max power	10 Pa ****
Minimum draught allowed for minimum power	5 Pa ****
Mass of smoke at Min and at Max	2.2 / 3.5 g/sec
Hopper capacity	26 l / 17 kg *
Fuel dimensions	Ø6mm L3÷40mm
Hourly consumption at Min and at Max	0.6 / 1.37 kg/h *
Autonomy at Min and at Max	27 / 12 h *
Heatable volume m ³	113 / 177 / 310 **
Combustion air inlet	Ø 60 mm
Air inlet	80 cm ²
Smoke outlet	Ø 80 mm
Nominal electrical power (EN 60335-1).	45 W (max 350 W)
Supply voltage and frequency	230 Volt / 50 Hz
Net weight	102 kg
Distance from combustible material (back/side/under)	150 / 150 / 0 mm
Distance from combustible material (front/ceiling)	800 / 1000 mm

* Data that may vary depending on the type of pellets used.

**Heatable volume based on the requested power per m³ (respectively 55-35-20 W/m³)

*** Flue gas temperature at the appliance outlet, to be used in the chimney sizing calculation (according to EN 13384-1)

**** Consider a minimum draught of 2 Pa in the EN 13384-1 chimney dimensioning calculations